Technical Datasheet

PSF 30

Polyester fabric for reinforcing waterproofing membranes

Description - Fields of application

Thin polyester fabric of 30 g/m^2. It is used in order to locally or totally reinforce waterproofing coatings (e.g. for ISOFLEX, etc.), in case the surface shows local or total cracks, as well as at wall-to-floor junctions, corners etc.

Technical data

Weight:	30 g/m^2
Material thickness:	0.23 mm
Tensile strength:	
- Long.:	55 N/5cm
- Trans.:	50 N/5cm
Elongation at break:	
- Long.:	20%
- Trans.:	20%
Shrinkage:	
- Long.:	2.0%
- Trans.:	0.8%

Packaging

1 m x 200 m rolls (200 m²), 1 m x 100 m rolls (100 m²), 10 cm x 50 m rolls.

Storage

Stored in its original, unopened packaging, protected from humidity and UV radiation.

ISOMAT S.A.
BUILDING CHEMICALS, MORTARS & PAINTS
HEADQUARTERS – THESSALONIKI, GREECE
17th km Thessaloniki – Ag. Athanasios Road
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece
T +30 2310 576000
www.isomat.eu e-mail: support@isomat.eu

The technical information and instructions supplied in this datasheet are based on the knowledge and experience of the Department of Research and Development of our company and on results from long-term applications of the product in practice. The recommendations and suggestions referring to the use of the product are provided without guarantee, since site conditions during the applications are beyond the control of our company. Therefore the user is responsible for confirming that the chosen product is suitable for the envisaged application. The present edition of this technical datasheet automatically cancels any previous one concerning the same product. | Edition: 03.06.2026