Technical Datasheet

PSF 60

Polyester fleece for reinforcing waterproofing layers

Description – Fields of application

PET crosslapped spunlace non-woven polyester fleece 60 g/m^2, used to enhance the strength and durability of various waterproofing membranes, such as ISOFLEX, ISOFLEX-PU 500 etc., over the entire surface to be waterproofed or across localized cracks, joints, wall-floor junctions, corners, etc.

Technical data

Weight:	60 g/m^2 (min. 54 – max. 66)
Thickness:	0.57 mm (min. 0.42 – max. 0.72)
Tensile strength: (NF EN 29073-3)	
- Machine direction (MD):	180 N
- Cross direction CD):	150 N
Elongation at break: (NF EN 29073-3)	
- Machine direction (MD):	20-75%
- Cross direction (CD):	30-95%

Packaging

1 m x 50 m rolls (50 m²), 10 cm x 50 m rolls.

Storage

Stored in its original, sealed packaging, protected from humidity and UV radiation.

ISOMAT S.A.
BUILDING CHEMICALS, MORTARS & PAINTS
HEADQUARTERS – THESSALONIKI, GREECE
17th km Thessaloniki – Ag. Athanasios Road
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece
T +30 2310 576000
www.isomat.eu e-mail: support@isomat.eu

The technical information and instructions supplied in this datasheet are based on the knowledge and experience of the Department of Research and Development of our company and on results from long-term applications of the product in practice. The recommendations and suggestions referring to the use of the product are provided without guarantee, since site conditions during the applications are beyond the control of our company. Therefore the user is responsible for confirming that the chosen product is suitable for the envisaged application. The present edition of this technical datasheet automatically cancels any previous one concerning the same product. | Edition: 03.06.2026